

Delivery forms

Edition 01/2012
Replaces edition 01/2010

for patented-drawn spring wires

		Wire diameter mm	Coils/Spools diameter		Wire weight in kg max.
			inside	outside	
Catch weight coil:					
wet drawn		0.50 - 1.00	200	360	40
		0.30 - 1.60	340	570	70
dry drawn		0.30 - 0.80	230	370	40
		0.80 - 1.40	390	550	80
		1.40 - 1.95	450	750	120
		2.00 - 3.40	560	980	600
		3.00 - 6.50	800	1050	700
Reel:					
Plastic	K 80	0.07 - 0.20	50	80	0,8
	K 100	0.10 - 0.20	63	100	1,5
	K 125	0.10 - 0.20	80	125	2,6
	K 250	0.07- 0.50	160	250	20
	K 355	0.20 - 0.60	224	355	40
Metal	B 600	0.30 - 0.80	300	600	130
	B 750	0.30 - 3.00	480	750	250
	B 760	0.30 - 3.00	430	760	400
Formed coil:					
Z 2		0.70 - 2.50	370	760	400
Z 3		1.50 - 3.50	670	1000	620
Core less coils		3.60 - 5,00	500	800	1500
Large coil		3,00 - 5,00	500	800	1800

